



THE **M**USES OF **L**IGHT
CALLIOPE-MELPOMENE-TERPSICORE-CLIO-POLYMNIA-ERATO-EUTERPE-TALIA-URANIA-AUREA
House of Desiri



ERATO

The Exagon



ERATO

The Exagon

OVERVIEW

The Muses of Light is the innovative range by De Sisti studied and designed to operate the best in cinema and location. The range offers the best solution for any situation possible, with luminaires that go from narrow spot to full flood and tunable CCT, from 2700 to 6500 K°. Every fixture has its own definite geometric shape, it is characterized by a very high energy efficiency, extreme versatility of use and can be operated both manually and via DMX.

The Lighting Fixture is DMX Controlled for:

- 0 to 100% with a super smooth Dimming (over 40.000 dimming points between 0 and 100)
- Super precise CONTINUOUS MODE for CCT control for every 50 K°.

The Muses of Light – ERATO, the HEXAGON, combines high-power input (360W) to a MEDIUM FLOOD optic, with a beam angle of 34 degrees that provides up to (max value) at 10 mt distance.

MODEL & ACCESSORIES	DESCRIPTION
6MH	Erato Medium Head and Yoke
DSE-300	DSE (Detachable Smart Electronics) - 300W
EC19P-10M	19 poles 10 m. Long Extension Cable including: - IN LINE 19 poles Male and Female Connector - Multicore Flexible Cable 10 m. long - adapt for DSE-300, DSE-500, DSE-1000
6MC	Transport case for ERATO Medium, includes: - Flight Case with Brakable Wheels



FEATURES

- Detachable driver, can operate in remote until 50 mt from the fixture (with optional extension cable)
- Conventional cooling (no fans)
- The driver automatically recognizes the Muse to which it is connected and adjusts the firmware accordingly
- Over 40.000 dimming points between 0 and 100%
- Immediate and super precise dimming response
- Rugged aluminium housing designed with advanced construction technologies, special "STARDUST" coating
- Wireless DMX as standard (LUMENRADIO TIMOTWO)
- Dmx in-out, powercon in-out
- 3 CCT Preset buttons in Storaro mode (3200, 4300 and 5500 K°)
- Optional accessories available
- LED power 2000W, Narrow spot optic



ERATO

The Exagon

TECHNICAL SPECIFICATIONS

Power to LED	360W - DC current to the LED - flicker free
Rated Voltage & PFC	90-250V 50-48Hz PFC 0,96 DC 48V
Power consumption	424W @ 230V 424W @120V
Power Connection	powerCON IN & OUT XLR Pin for battery operation
DMX Channels	8 bit: 7 to 9 (depending if Mode control and Fan control are activated) 39 in Extended mode 16 bit: 8 to 10 (depending if Mode control and Fan control are activated) 40 in Extended mode
DMX Channels	2 @ 8bit 3 @ 16bit
LED ARRAY Lifetime	50.000 hours with 80% Lumen Maintenance. The LED BOARDS are tested and certified up to LM80
CCT	Tunable from 2.800°K to 6.600°K
GRI / TLCI	CRI>95 TLCI:96
Protection Type	Min. IP23 (IP rating test shortly available)
Ambient operating Temperature	-20° C to +45° C (-4° to 113°F)
Weight of Fixture	Head 16 Kg – Driver 2,5 Kg
Size	70 cm x 60 cm 670 mm x 770 mm x 140 mm with driver or 120 mm only head 26.37" x 30.31" x 5.51" (with driver) - 4.72" (only head)
Optic	Medium Flood 34°
Illumination at 10 mt distance	95 Fc

DIMENSIONS

